

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

- **1.1 Product identifier:** For professional use only
- **Trade name:** PQ32 2 Pack Etch Primer Activator
- **Article number:** PQ32
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**
 Surface Coating
 Surface Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
 Phoenix Precision Paints Limited
 13 Orwell Court,
 Wickford,
 Essex SS11 8YJ
 Tel +44 (0)1268 730549
 EMAIL: sales@phoenix-paints.co.uk
- **Further information obtainable from:** sales@phoenix-paints.co.uk
- **1.4 Emergency telephone number:** +44 (0)1268 730549 (Business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS05 corrosion

Eye Dam. 1

H318 Causes serious eye damage.



GHS07

Acute Tox. 4
 Skin Irrit. 2
 STOT SE 3

H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Safety data sheet according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms** GHS02, GHS05, GHS07, GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Xylene (mixed isomers)

isobutanol

- **Hazard statements**

Flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition / Information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|--------------------------------------|----------------------------|-----------|
| CAS: 90989-38-1 EINECS: 292-694-9 | Xylene (mixed isomers) | 50 - 100% |
| CAS: 78-83-1 EINECS: 201-148-0 | isobutanol | 10-25% |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

SECTION 4: First Aid Measures

4.1 Description of first aid measures

• **General information:** Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident..

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

Immediately rinse with water.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

• **After swallowing:**

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Fire Fighting Measures

• **5.1 Extinguishing media**

• **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **For safety reasons unsuitable extinguishing agents:** Water with full jet

• **5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

• **5.3 Advice for firefighters**

• **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental Release Measures

• **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

• **6.2 Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

SECTION 7: Handling and Storage

• **7.1 Precautions for safe handling**

Ensure good ventilation/extraction at the workplace.

Hygiene measures:

Wash hands before breaks and at the end of workday.

Use protective skin cream before handling the product.

• **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

• **7.2 Conditions for safe storage, including any incompatibilities**

• **Storage:**

• **Requirements to be met by storerooms and receptacles:** No special requirements.

• **Information about storage in one common storage facility:** Not required.

• **Further information about storage conditions:**

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

• **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure Controls / Personal Protection

• **Additional information about design of technical facilities:** No further data; see item 7.

• **8.1 Control parameters**

• **Ingredients with limit values that require monitoring at the workplace:**

90989-38-1 Xylene (mixed isomers)

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm |
|-----|--|

78-83-1 isobutanol

| | |
|-----|---|
| WEL | Short-term value: 231 mg/m ³ , 75 ppm Long-term value: 154 mg/m ³ , 50 ppm |
|-----|---|

• **DNELs**

90989-38-1 Xylene (mixed isomers)

| | | |
|------------|------|--|
| Oral | DNEL | 1.6 mg/day (Con) |
| Dermal | DNEL | 108 mg/day (Con) 180 mg/day (Ind) |
| Inhalative | DNEL | 14.8 mg/m ³ (Con) 77 mg/m ³ (Ind) |

78-83-1 isobutanol

| | | |
|------------|------|---|
| Oral | DNEL | 25 mg/day (Con) |
| Inhalative | DNEL | 55 mg/m ³ (Con) 310 mg/m ³ (Ind) |

• **Additional information:** The lists valid during the making were used as basis.

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

• **8.2 Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• **Respiratory protection:**

When spraying the product, use a respiratory protective device.

If spraying this product, an ABEK respirator to EN141 and EN405 is normally sufficient. If in doubt, consult a respirator manufacturer and show this safety data sheet.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and Chemical Properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid

Colour: Clear

• **Odour:** Characteristic

• **Odour threshold:** Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 108 °C

• **Flash point:** 24 °C

• **Flammability (solid, gaseous):** Not applicable.

• **Ignition temperature:** 390 °C

• **Decomposition temperature:** Not determined.

• **Self-igniting:** Product is not selfigniting.

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

| | |
|---|---|
| • Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| • Explosion limits: | |
| Lower: | 1.0 Vol % |
| Upper: | 12.0 Vol % |
| • Vapour pressure at 20 °C: | 12 hPa |
| • Density at 20 °C: | 0.851 |
| • Solubility in / Miscibility with water: | NOT MISCIBLE |
| • Partition coefficient (n-octanol/water): | Not determined. |
| • Viscosity: | |
| Dynamic at 20 °C: | Not determined. |
| Kinematic: | Not determined. |
| • Solvent content: | |
| Organic solvents: | 23.4 % |
| Water | 0.1% |
| Solids content: | 0.5 % |
| • 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and Reactivity

- **10.1 Reactivity:** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions:** No dangerous reactions known.
- **10.4 Conditions to avoid:** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological Information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.

• **LD/LC50 values relevant for classification:**

90989-38-1 Xylene (mixed isomers)

| | | |
|------------|----------|-------------------|
| Oral | LD50 | 3523 mg/kg (Rat) |
| Dermal | LD50 | 12126 mg/kg (Rab) |
| Inhalative | LC50/4 h | 27000 mg/l (Rat) |

78-83-1 isobutanol

| | | |
|--------|------|-------------------|
| Oral | LD50 | >2000 mg/kg (Rat) |
| Dermal | LD50 | >2000 mg/kg (Rab) |

Safety data sheet according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**
Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

SECTION 12: Ecological Information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal Considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport Information

- | | |
|---------------------------------------|---|
| • 14.1 UN-Number | |
| • ADR, IMDG, IATA | UN1263 |
| • 14.2 UN proper shipping name | |
| • ADR | 1263 PAINT RELATED MATERIAL (not viscous) |
| • IMDG | PAINT RELATED MATERIAL |
| • IATA | PAINT RELATED MATERIAL |

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

- 14.3 Transport hazard class(es)
- ADR, IMDG, IATA



- Class 3 Flammable liquids.
- Label 3

- 14.4 Packing group III
- ADR, IMDG, IATA

- 14.5 Environmental hazards:
- Marine pollutant: No

- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E,S-E
- Stowage Category A

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

• Transport/Additional information:

- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL (NOT VISCOUS), 3, III

SECTION 15: Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 28, 29

• National regulations:

• Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 23.4 |

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name: PQ32 2 Pack Etch Primer Activator

SECTION 16: Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

- **Department issuing SDS:** Product safety department: LABORATORY

- **Contact:** Health & Safety Officer

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1